

## AMBER ONYX

APPLICATION		SPECIFICATIONS
<b>ABRASION RESISTANCE</b>	<b>COLOR ENHANCING</b>	CATEGORY
	Yes	Onyx
	<b>COUNTERTOPS/ VANITIES</b>	THICKNESS
STAIN RESISTANCE	Yes	2 C M
	<b>INTERIOR FLOOR</b>	FINISH
	Yes	Polished
ETCHING RESISTANCE	<b>FIREPLACE/ INTERIOR WALL</b>	GROUP
	Yes	High End
	SHOWER WALL	<b>COUNTRY OF ORIGIN</b>
HEAT RESISTANCE	Yes	Italy
	SHOWER FLOOR	TRANSLUCENT
	Yes	Yes
	<b>EXTERIOR FLOOR</b>	PATTERN
	No	Book Match
<section-header></section-header>	EXTERIOR WALL	CUT TO SIZE
	No	Yes
	<b>POOL/ FOUNTAIN</b>	AVERAGE SIZE
MOVEMENT INDEX	No	106 X 70
	FURNITURE TOP	SEALER
	Yes	Filamp90 or Mapei Ultra Care



- \* For cleaning, as needed, use a neutral cleanser to scrub tile and grout.
- \* Wipe up spills immediately. Dry with a second soft towel or cloth.
- \* Do not use bleach, ammonia based cleansers, acidic, citrus or other harsh chemicals.
- \* Do not use gritty cleansers of soft scrubs that are abrasive and rough scouring pads.



