



YUKON WHITE

APPLICATION

SPECIFICATION

ABRASION RESISTANCE



STAIN RESISTANCE



ETCHING RESISTANCE



HEAT RESISTANCE



UV RESISTANCE



COLOR RANGE



MOVEMENT INDEX



COLOR ENHANCING

No

COUNTERTOPS/ VANITIES

Yes

INTERIOR FLOOR

Yes

FIREPLACE/ INTERIOR WALL

Yes

SHOWER WALL

Yes

SHOWER FLOOR

Yes

EXTERIOR FLOOR

Yes

EXTERIOR WALL

Yes

POOL/ FOUNTAIN

Yes

FURNITURE TOP

Yes

CATEGORY

GRANITE

THICKNESS

3 CM

FINISH

Polished/Leather

AVERAGE SIZE

122x75

GROUP

BASIC

TRANSLUCENT

NO

PATTERN

Slip Match

CUT TO SIZE

Yes

SEALER

NA

ORIGIN

India

MAINTENANCE AND CARE

- * For cleaning, as needed, use a neutral cleanser to scrub tile and grout.
- * Wipe up spills immediately. Dry with a second soft towel or cloth.
- * Do not use bleach, ammonia - based cleansers, acidic, citrus or other harsh chemicals.
- * Do not use gritty cleansers or soft scrubs that are abrasive and rough scouring pads.

